IS15X


The IS15X is a versatile performer for a wide variety of install applications

The IS15X utilizes a 1000 watt 15-inch, low-frequency driver for substantial bass response. A 2-inch HF compression driver, coupled to MacPherson's slot-CD horn, provides transparent highs with wide coverage.

Designed with easy installation in mind

The low-profile cabinet (just over 8-inches deep!) includes rigging points on multiple sides, a powder-coated steel grill, and a choice of black or paintready finish. Connectors include a Neutrik NL4, plus two barrier strips—one on the back and one on the front under the grill—ideal for testing, or for use in wall-mounted applications.

- **Features** Low-profile enclosure for small visual profile
 - Dual barrier strips for easy connection and testing
 - High power handling
 - Convenient rigging points for easy suspension
 - Rotatable slot-CD horn for smooth, wide high-frequency dispersion
 - Ideal for churches, meeting rooms, auditoriums, multimedia systems, screening rooms, and a variety of applications



IS15X

IS15X Specifications

Standard Configuration

IS15X: Bi-amp

Frequency Response

 ± 3 dB, 85Hz to 15kHz ± 5 dB, 60Hz to 17kHz

Coverage (between -6dB points)

Horizontal: 90 degrees Vertical: 55 degrees

HF component rotates for alternate pattern selection

Nominal Impedance

LF: 8 ohms HF: 8 ohms

Sensitivity

LF: 98dB, one watt, one meter HF: 106dB, one watt, one meter

Maximum SPL

127dB, broadband, one meter, one minute

Recommended Amplifier Power

LF: 600 to 1000 watts HF: 120 to 200 watts RMS into 8 ohms

Recommended Crossover Point

1kHz, 24dB per octave

Connectors

One, Neutrik NL4; two, barrier strips

Suspension/Attachment Points

Ten, 5/16-18 threads

Enclosure

Hardwood plywood, textured black or paint-ready finish, powder-coated perforated steel grill with open-cell foam backing, recessed connector plate, front-to-back wirepass raceway

Dimensions

30.2 inches high (76.8cm) 17.2 inches wide (43.6cm) 8.4 inches deep (21.3cm)

Weight

73.5 pounds (33.4kg)

Options

Paint-ready finish, weatherproofing, Black Box Stereo Analog Controller unit, CCM Control Card for Crown P.I.P.®-compatible amplifiers

Warranty

Three years from date of original purchase

Contents subject to change without notice. Dimensions provided for general reference only.

